

2K-EP VERDÜNNUNG

PRODUCT DESCRIPTION

Universal thinner for all 2-component epoxy resin primers and lacquers.

QUALITIES

- free from aromatics
- highly volatile
- universally applicable

PACKAGING SIZES

5 l, 30 l

STORAGE

2 years if stored cool and dry in the well-sealed original container.

Hazard class acc. to VbF: A II

TECHNICAL DATA

Density: 0.864 +/- 0.05 g/m³
 Flashpoint: +26 °C
 Explosion limits: lower 1,2%
 upper 11,0%
 Steam pressure: 14.4 mbar; 20°C
 Boiling point: 108 - 128 °C

HAZARD DESIGNATION

acc. to regulation (EG) Nr. 1272/2008 (CLP)



Gefahr

TRANSPORT

hazard class acc. to ADR/RID 3, III UN 1263

DISPOSAL

Exclusively completely emptied containers can be disposed of in the collection and recycling system. Containers with residual product need to be collected in waste disposal stations.

Special waste identification number: 55508 acc. to ÖNORM S 2100
 EU waste category no.: 080111

SAFETY NOTES

The product is to be used for the intended purpose only. This product is a hazardous concoction in accordance with the Chemicals Act and therefore subject to labelling. Further information on the handling of the product can be gathered from the EG-Safety Data Sheet. The EG-Safety Data Sheet is available for the commercial user on our website www.okalin.at.

NOTICE

The information on this data sheet complies with our current state of knowledge and is intended to inform about our product and its applicability. This technical information however does not relieve the purchaser/user of his responsibility to test our products for their suitability under the applicable circumstances for the intended end use. No liability can be derived from it.

THIS DATA SHEET REPLACES ALL PREVIOUS VERSIONS.

Wir (be)kennen Farbe